

## WAX-IMPREGNATED TOWELETTE

### FIELD OF THE INVENTION

This invention relates to a disposable fabric sheet impregnated with car wax. More particularly, this invention relates to a low-lint fabric sheet impregnated with a silicone-based aqueous car wax emulsion and a silicone polyether wetting agent.

### BACKGROUND OF THE INVENTION

A number of products are available for polishing and waxing cars. Typically these materials are paste or liquid wax formulations. The waxes are applied by wiping a cloth over the wax surface and rubbing the wax onto the vehicle or by pouring a liquid wax onto the cloth or vehicle and rubbing the wax over the surface of the vehicle. Such products generally require that the wax be allowed to dry for a period of time. Then the surface of the vehicle must be buffed to remove excess wax and polish the surface. Unlike wax-based products, car waxing formulations based on silicone oil do not require buffing.

U.S. Patent No. 4,683,001 to Floyd *et al.* discloses a one step dry-and-shine polishing cloth for polishing a pre-washed, wet automobile surface. The cloth simultaneously polishes the car and dries the surface. The Floyd *et al.* polishing cloth is a dry product which comprises a non-woven polyolefin fabric sheet, such as a melt-blown polypropylene fabric sheet that is discontinuously coated with a formulation of saponified and non-saponified waxes and silicone oils. The wax formulations disclosed by Floyd *et al.* are generally high solids water-in-oil emulsions that are printed onto the fabric in a pattern that covers generally about 9 to 25 percent of the surface of the fabric, utilizing gravure printing methods and the like. The wax components of the polishing compositions of Floyd *et al.* comprise about 5 to 50% of the formulation on a weight basis. Although the polishing cloths of Floyd *et al.* eliminate the need for buffing, they do require that the automobile surface be wet prior to application of the wax.

Polishing a dry, lightly soiled automobile surface is generally problematic, since the soil particles abrade the finish of the car causing

undesirable scratch marks, thus it is generally a requirement that car waxes be applied to a clean surface. It would be desirable to provide a car polishing product that can be applied to a dry, lightly soiled surface without scratching the finish of the vehicle, and that does not require buffing.

5 **SUMMARY OF THE INVENTION**

A moist, wax-impregnated towelette, suitable for polishing a lightly dirty automobile exterior surface without abrading the vehicle finish, is a low-lint fabric sheet substantially uniformly impregnated with an aqueous silicone-based wax emulsion containing a silicone polyether wetting agent, which is a dialkylsiloxane-alkylene oxide copolymer. The wax-impregnated towelette of the present invention preferably comprises a sheet of low-lint fabric, such as melt-blown polypropylene non-woven fabric, impregnated with about 30 grams to 170 grams of an aqueous silicone based wax emulsion per square meter of fabric.

The aqueous silicone-based car wax emulsions of the present invention contain a silicone oil, such as polydimethylsiloxane, an amino-functional silicone, such as an aminoethylaminopropylsiloxane - dimethylsiloxane copolymer, isopropanol, nonionic and cationic emulsifiers, anti static agent, and a silicone polyether wetting agent, such as an ethylene oxide-dimethylsiloxane copolymer and a wax, such as carnauba wax. The car wax emulsions may optionally contain small amounts of UV absorbers, solvents such as mineral oil and butyl cellosolve, fragrances, preservatives, additional wetting agents, anti-foaming agents, and neutralizing agents such as mineral acids or organic acids, and the like.

The silicone-based wetting agent component of the aqueous silicone-based car wax emulsions provides for a substantially uniform distribution of the wax emulsion into the fabric sheet. In addition, the wetting agent aids in the application of the car wax to the exterior surface of a vehicle when the impregnated sheet is wiped across the vehicle surface. The amino-functional silicone components for the formulations provide strength and durability to the wax film after application to the vehicle surface. The fabric sheet material is chosen so as to minimize streaking and to minimize lint deposits on the finish of the vehicle during the polishing process. A high-gloss protective film,

substantially free of lint, is thus obtained, without the need for buffing or additional wiping away of excess polish as is generally required with car wax application. Because of the high lubricity of the silicone-based wax formulation, the wax-impregnated towelettes of the present invention may be utilized to polish a dry, lightly soiled vehicle surface without washing and without abrading or scratching the vehicle finish.

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

A moist, wax-impregnated towelette, suitable for polishing a lightly dirty automobile exterior surface without washing and without abrading the vehicle finish comprises a low-lint fabric sheet impregnated with an aqueous silicone-based wax emulsion and a silicone polyether wetting agent.

As used herein, the term "silicone" and grammatical variations thereof means a polymer having the general formula  $(R_nSiO_{((4-n)/2)})_m$  wherein n is between 0 and 3 and m is 2 or greater, as defined in *Silicone Compounds Register and Review*, 5th Edition, R. Anderson, G. L. Larson and C. Smith Eds., Hüls America Inc., Piscataway, New Jersey, p 247 (1991). Silicones may be linear or branched. The term "amino functional silicone" and grammatical variations thereof means a silicone as defined above, wherein the alkyl or aryl group is substituted with a primary, secondary or tertiary amino group. The term "silicone-based" as used herein means a material that contains a silicone component.

The term "car wax" and grammatical variations thereof, as used herein, means a composition suitable for polishing the exterior surface of a vehicle such as a car, truck, motorcycle, or the like. As used herein, the term "wax-impregnated towelette" means a disposable sheet of pliant material impregnated or coated with a car wax formulation, of a size suitable for hand application of car wax to a vehicle surface. The term "low-lint" means a fabric that does not leave a visible deposit of fibers on a vehicle surface when utilized for application of car wax.

When referred to herein, the viscosity of a liquid component of the invention is quoted as a kinematic viscosity in centistokes (cSt), measured at 25 °C (77 °F) unless otherwise specified.

Fabric sheet materials useful for the wax-impregnated towelettes of the present include any low-lint fabric. Preferably, the low-lint fabric is a melt-blown polypropylene fabric such as described in U.S. Patent No. 4,683,001 to Floyd *et al.*, the relevant disclosures of which are incorporated herein by reference. The fabric sheets generally have a weight of about 20 grams per square meter (0.75 ounce per square yard) to about 200 grams per square meter (6 ounces per square yard), preferably about 33 grams per square meter (1 ounce per square yard). Also suitable are substantially low-lint fabrics such as polyurethane-coated polyester fabrics.

Preferably, the silicone-based car wax useful with the wax-impregnated towelettes of the present invention is an aqueous emulsion containing about 1 to about 5 weight percent isopropanol, about 0.5 to about 1 weight percent of a silicone oil, about 0.01 to about 1 weight percent of an amino functional silicone, about 0.001 to about 0.15 weight percent of a wax, about 0.05 to about 0.15 weight percent of a cationic emulsifier, about 0.01 to about 0.08 weight percent of a nonionic emulsifier, about 0.01 to about 0.1 weight percent of an antistatic agent, and about 0.05 to about 0.5 weight percent of a silicone polyether wetting agent.


Preferred silicone oils are  $C_1 - C_{18}$  alkyl or  $C_6 - C_{10}$  aryl substituted polysiloxanes, more preferably poly( $C_1 - C_4$  dialkyl)siloxanes. Most preferably, the silicone oil is a polydimethylsiloxane. The silicone oils useful in the car wax emulsions of the present invention preferably comprise a silicone oil, or a mixture of silicone oils, having a viscosity in the range of about 10 centistokes (cSt.) to about 60,000 cSt, more preferably about 10 cSt to about 5000 cSt, most preferably about 10 cSt to about 1000 cSt. Silicone oils are commercially available from a variety of manufacturers such as GE Silicones of Waterford, New York and Dow Corning Corporation of Midland, Michigan.

Amino-functional silicones useful in the present invention include silicone polymers which contain primary, secondary or tertiary amino functional groups. Preferably the amino-functional silicones are copolymers of dialkylsiloxane and amino-functional siloxane comonomers. Preferably the amino-functional silicones contain about 1 to about 50 mole percent of amino-


functional siloxane comonomer units, more preferably about 1 to about 30 mole percent of amino-functional siloxane comonomer units. These silicone fluids may contain starting materials and reaction by-products in addition to the amino-functional dialkylpolysiloxane. Suitable amino-functional silicones include those disclosed in co-owned U.S. Patent No. 4,665,116 to Kornhaber *et al.*, the pertinent disclosures of which are incorporated herein by reference.

A useful amino-functional dialkylpolysiloxane, for example, can be derived from the equilibration of a polydialkylsiloxane having a viscosity of about 1 to about 30,000 cSt and an amino-functional silane or siloxane in the presence of a basic catalyst. Typical polydialkylsiloxanes useful for the preparation of amino-functional silicones include cyclic dimethylsiloxane oligomers having about 3 to about 10 dimethylsiloxane monomer units.

The amino-functional silanes or siloxanes, which are reacted with the dialkylpolysiloxanes may be represented by the general formula (I):



wherein G represents the radicals R, OR", NR', or OSiR<sub>3</sub> in which R is C<sub>1</sub> - C<sub>18</sub> alkyl or C<sub>6</sub> - C<sub>10</sub> aryl, R' represents hydrogen or monovalent hydrocarbon radicals having 1 to about 18 carbon atoms, R" is a substituted or unsubstituted divalent C<sub>1</sub> - C<sub>18</sub> hydrocarbon radical, a substituted or unsubstituted divalent alkyleneoxy group in which the oxygen provides an ether linkage, or an unsaturated divalent C<sub>4</sub> - C<sub>18</sub> hydrocarbon radical; Q represents the radicals:



Z is a radical selected from the group consisting of R<sub>3</sub>SiO<sub>0.5</sub>, and R'<sub>2</sub>NR''O<sub>0.5</sub> in which R, R' and R" are the same as above, a is a number having a value of about 0 to about 2; b is a number having a value of about 0 to about 3; and x is a number having a value of about 1 to 20,000. Preferably, R' is hydrogen.

Illustrative divalent radicals represented by R" are hydrocarbon radicals having from 2 to 18 carbon atoms such as ethylene, trimethylene,


tetramethylene, hexamethylene, octamethylene; alkyleneoxy group radicals having the formulas:  $(-\text{OC}_2\text{H}_4-)_r$ ,  $(-\text{OC}_2\text{H}_4\text{OCH}_2-)_r$  and  $(-\text{OC}_3\text{H}_6-)_r$  in which r is a number having a value of about 1 to about 50, such as ethylene oxide, trimethylene oxide and polymers thereof and alkylene radicals such as vinylene, propenylene, butenylene, hexenylene and the like.

Examples of suitable amino-functional silanes include but are not limited to:


2-aminoethyltriethoxysilane,  
3-aminopropyltrimethoxysilane,  
(3-(2-aminoethylamino)propyl)methyldimethoxysilane,  
6-aminohexyltributoxysilane,  
6-(2-aminoethoxy)hexyltriethoxysilane,  
4-(3-aminopropoxy)butyltributoxysilane, and the like.

Useful amino-functional dialkylpolysiloxanes and methods for preparing them are described in U.S. Patent Nos. 3,890,269, 3,960,575 and 4,247,330 the pertinent disclosures of which are incorporated herein by reference.

Preferred amino-functional silicones are polymers comprising repeating units represented by the general formula (II):



wherein Q represents the radicals:



R is  $\text{C}_1 - \text{C}_{18}$  alkyl or  $\text{C}_6 - \text{C}_{10}$  aryl; R' represents hydrogen or monovalent hydrocarbon radicals having 1 to about 18 carbon atoms; R'' is a substituted or unsubstituted divalent  $\text{C}_1 - \text{C}_{18}$  hydrocarbon radical, a substituted or unsubstituted divalent alkyleneoxy group in which the oxygen provides an ether linkage, or an unsaturated divalent  $\text{C}_4 - \text{C}_{18}$  hydrocarbon radical; p is number having a value in

the range of about 1 to about 2; q is a number having value in the range of about 1 to about 2000; and y is a number having value in the range of about 0 to about 2000; with the proviso that the sum of q and y is at least about 15.

Examples of suitable amino-functional silicones include

5

(2- aminoethyl)methylpolysiloxane,  
(3-aminopropyl)methylpolysiloxane,  
(2-aminoethyl-3-aminopropyl)methylpolysiloxane,  
(3-(2-aminoethoxy)propyl)methylpolysiloxane,  
(6-aminoethyl)methylpolysiloxane,  
10 (3-(2-aminoethoxy)propyl)methylpolysiloxane,  
(3-(2-aminoethylamino)propyl)methylsiloxane,  
dimethylsiloxane copolymers thereof, and the like.

10

15

Useful amino-functional dialkylpolysiloxanes and methods for preparing them are described in U.S. Pat. Nos. 3,890,269, 3,960,575 and 4,247,330 whose pertinent disclosures are incorporated herein by reference.

20

A preferred amino-functional polydimethylsiloxane is commercially available under the designation SF-1706 from GE Silicones, Waterford, N.Y., and is a mixture of aminoethylaminopropylpolysiloxane, having Chemical Abstract Service (CAS) Registry No. 67923-07-3 and methoxy-terminated dimethylsiloxane polymers having CAS Registry No. 68440-84-6, according to the manufacturer's Material Safety Data Sheet (MSDS) for the product. Other suitable amino-functional silicones are available from GE Silicones, of Waterford, New York and OSi Specialties, Inc. of Danbury, Connecticut.

25

Waxes suitable for use in the wax-impregnated towelettes of the present invention include vegetable waxes such as carnauba, candelilla, and ouricury; mineral waxes such as montan, paraffin, and microcrystalline waxes; animal waxes, such as, beeswax; silicone waxes; and mixtures thereof. A vegetable wax such as carnauba wax is particularly preferred.

30

Cationic and nonionic emulsifiers useful in the aqueous silicone-based car wax emulsions of the present invention include cationic surfactants such as described in the review on surfactants by Cahn and Lynn, "Surfactants and

Deterative Systems" *Kirk-Othmer Encyclopedia of Chemical Technology*, 3rd Edition, Volume 22, John Wiley & Sons, New York, pp. 332 - 432 (1983), the relevant disclosures of which are incorporated herein by reference. An extensive listing of cationic and nonionic surfactants and commercial sources thereof can be found in *McCutcheon's, Volume 1: Emulsifiers & Detergents*, 2001 North American Edition, McCutcheon's Division, The Manufacturing Confectioner Publishing Co., Rock Glen, New Jersey (2001), the relevant disclosures of which are incorporated herein by reference.

Preferred cationic emulsifiers include an amine, an aliphatic or rosin amine ethoxylate, an amidoamine, and a quaternary ammonium salt. Amphoteric detergents that display cationic properties below about pH 7 can also be used.

Typical amine cationic emulsifiers include amines derived from fatty acids and rosins such as hydrogenated tallow amine, stearyl amine, lauryl amine, and the like, which are typically commercially available as acetate, oleate or naphthalenate salts. Other useful amine cationic emulsifiers include N-alkyltrimethyleneamines having the general formula  $R^*NHCH_2CH_2CH_2NH_2$ , wherein  $R^*$  is an alkyl group derived from natural oils such as coconut, tallow and soybean oils and the like; 2-alkylimidazolines, such as 2-heptadecylimidazoline, 2-heptadecenylimidazoline and the like; and 1-aminoethyl 2-alkyl imidazolines.

Typical commercially available aliphatic and rosin amine ethoxylate cationic emulsifiers include  $C_6$  to  $C_{20}$  alkyl amines and rosin amines that have been ethoxylated with about 2 to about 50 moles of ethylene oxide per mole of amine, such as cocoamine, soyamine or stearylamine ethoxylated with 2 to 15 moles of ethylene oxide per mole of amine.

Typical amidoamine cationic emulsifiers include condensation products of fatty carboxylic acids with di- and polyamines, such as condensates of diethylenetriamine with stearic, oleic, coconut, or tall oil fatty acids, and the like.

Typical quaternary amine cationic emulsifiers include dialkyldimethylammonium salts, such as dicocodimethylammonium chloride,

distearyldimethylammonium chloride, and the like;  
alkylbenzyldimethylammonium chlorides such as cocobenzyldimethylammonium  
chloride, tallowbenzyldimethylammonium chloride,  
stearylbenzyldimethylammonium chloride and the like; and  
5 alkyltrimethylammonium salts such as cetyltrimethylammonium chloride,  
myristyltrimethylammonium bromide and the like; wherein the alkyl groups are  
derived from fatty amines and rosin amines.

Particularly preferred cationic emulsifiers include fatty amines and  
rosin amines such as hydrogenated tallow amine, and rosin amine ethoxylates,  
10 such as N,N-bis(2-hydroxyethyl)cocamine.

Preferred nonionic surfactants useful in the compositions and  
methods of the present invention include an alcohol alkoxylate, a polyol ester of a  
fatty acid, a polyoxyethylene ester of a fatty acid, a fatty acid amide, a  
polyoxyethylene fatty acid amide, a polyalkylene oxide block copolymer, an  
15 ethoxylated alkyl mercaptan, an ethoxylated anhydrosorbitol ester, an alkyl  
polyglycoside, and mixtures thereof.

Typical alcohol alkoxylates include ethoxylated C<sub>6</sub> to C<sub>18</sub> linear and  
branched alcohols, ethoxylated with about 2 to about 80 moles of ethylene oxide,  
such as ethoxylated lauryl alcohol, ethoxylated stearyl alcohol, and ethoxylated  
20 mixtures of C<sub>6</sub> - C<sub>18</sub> alcohols, and alkoxylated natural alcohols such as ethoxylated -  
propoxylated pine oil, ethoxylated soya sterol, and the like.

Typical polyol esters of fatty acids include saturated fatty acid  
monoglycerides, such as glycerol monolaurate, glycerol monococo ester, glycerol  
monotallow ester, glycerol monostearate, and the like; saturated fatty acid  
25 diglycerides, such as glycerol distearate, glycerol dilaurate and the like; unsaturated  
fatty acid monoglycerides, such as glycerol monooleate, glycerol monoricinoleate,  
and the like; unsaturated fatty acid diglycerides, such as glycerol dioleate, glycerol  
dilinoleate, and the like; glycol esters of fatty acids, such as propylene glycol  
monostearate, ethylene glycol monostearate, ethylene glycol monolaurate,  
30 diethylene glycol monooleate, diethylene glycol monostearate, and the like; and  
anhydrosorbitol fatty acid esters, such as mono, di and tri esters of 1,4-sorbitan with  
fatty acids such as stearic acid, palmitic acid and oleic acid.

Typical polyoxyethylene esters of fatty acids are polyethylene glycol mono- and di-esters of fatty acids comprising a polyethylene glycol portion having from about 5 to about 30 ethyleneoxy units, esterified at one or both ends with fatty acids such as stearic acid, lauric acid, oleic acid, and mixed fatty acids derived from natural oils such as coconut oil, castor oil, tall oil, and the like.

Typical fatty acid amides include diethanolamine fatty acid condensates such as coco diethanolamide, lauric diethanolamide, tall oil diethanolamide, and the like, and monoalkanolamine fatty acid condensates such as coco monoethanolamide, lauric monoethanolamide, stearic monoisopropanolamide, oleic monopropanolamide, and the like.

Typical polyoxyethylene fatty acid amides are ethoxylated mono and dialkanolamides having from about 2 to about 50 ethylene oxide groups, including ethoxylated lauric monoisopropanolamide, ethoxylated stearic diethanolamide, ethoxylated myristic monoethanolamide, ethoxylated oleic diethanolamide, and the like.

Typical polyalkylene oxide block copolymers include copolymers of ethylene oxide and propylene oxide initiated by ethylene glycol, propylene glycol, trimethylol propane, and the like, and have either linear or branched structures, depending on whether the initiator has two or three hydroxyl groups, respectively.

Typical ethoxylated alkyl mercaptans, include linear or branched alkyl mercaptans such as dodecylmercaptan, ethoxylated with 2 to 10 moles of ethylene oxide.

Typical ethoxylated anhydrosorbitol esters are mono, di and tri esters of 1,4-sorbitan with fatty acids such as stearic acid, palmitic acid and oleic acid that have been ethoxylated with about 4 to about 20 moles of ethylene oxide per mole of anhydrosorbitol ester.

Typical alkyl polyglycosides are glycosides (acetals) of  $C_6 - C_{20}$  alcohols with a monosaccharide such as glucose, fructose, lactose, mannose, xylose and the like or a polysaccharide or oligosaccharide such as isomaltose, maltose, cellobiose, mellobiose, maltotriose and the like.

Particularly preferred nonionic emulsifiers include sorbitan esters such as sorbitan monolaurate (e.g., Span® 20, available from Uniqema,

Wilmington, DE), ethoxylated anhydrosorbitol esters such as monooleylanhydrosorbitan ethoxylated with 20 moles of ethylene oxide per mole of sorbitan (e.g., Tween® 80, available from Uniqema, Wilmington, DE) and linear alcohol ethoxylates up to 9 moles of ethylene oxide per mole of alcohol (e.g., Neodol® 1-9, available from Shell Chemical Co., Houston, TX), and the like.

Suitable antistatic agents useful in the aqueous silicone-based car wax emulsions of the present invention include quaternary fatty acid amine condensates, polyamine resins, fatty amines, amides, fatty acid esters and other materials as described in the article "Antistatic Agents" by Zeeve Gur-Arieh and Bertie J. Reuben in *Kirk-Othmer Concise Encyclopedia of Chemical Technology*, John Wiley & Sons, New York, pp. 130-131 (1985), the disclosures of which are incorporated herein by reference. A particularly preferred antistatic agent is Larostat® 264A, available from BASF Corp., Mount Olive, NJ, which is a modified soyadimethylethylammonium ethosulfate. Other suitable antistatic agents are water-soluble quaternary compounds.

Preferred silicone polyether wetting agents for use in aqueous silicone-based car wax emulsions are block copolymers having at least one polyalkylene oxide block, such as polyethylene oxide, polypropylene oxide, mixtures thereof, and the like, and at least one poly(C<sub>1</sub> - C<sub>4</sub> dialkyl)siloxane, such as polydimethylsiloxane. Most preferred are copolymers of ethylene oxide and dimethylsiloxane.

Particularly preferred silicone polyethers are copolymers of ethylene oxide and dimethylsiloxane that are commercially available from GE Silicones of Waterford, New York, OSi Specialties, Inc. of Danbury, Connecticut and Dow Corning Corporation of Midland, Michigan. The polymers may have a linear block structure with alternating polyalkylene oxide and polydimethylsiloxane blocks or the polyalkylene oxide blocks may be grafted onto a polydimethylsiloxane backbone.

Optional components of aqueous silicone-based car wax emulsions useful in the wax-impregnated towelettes of the present invention include UV absorbers such as benzotriazoles, benzophenones, and the like; polymeric UV

absorbers having a UV chromophore attached to a polymer backbone, solvents such as mineral oil and butyl cellosolve, fragrances, preservatives, additional wetting agents, anti-foaming agents, neutralizing agents such as mineral acids or organic acids as well as polishing agents such as aluminum oxide, calcined clay, alkali and alkaline earth carbonates, and the like. The optional components may comprise up to about 15 weight percent of the aqueous silicone-based car wax emulsion, usually about 1 weight percent.

Preferably, the aqueous silicone-based car wax emulsion of the present invention contains silicone oil and amino-functional silicone in a weight ratio of about 1:1 to about 10:1, more preferably about 6:1. The preferred weight ratio of silicone oil to silicone polyether wetting agent is about 2:1 to about 5:1, more preferably about 3:1.

Preferably the cationic emulsifier is present in the car wax emulsion in a ratio of silicone oil to cationic emulsifier of about 5:1 to about 10:1, more preferably about 8:1. The nonionic emulsifier is preferably present in the car wax emulsion in a ratio of silicone oil to nonionic emulsifier of about 10:1 to about 30:1, more preferably about 20:1.

Preferably, the aqueous silicone-based car wax emulsions useful in the wax-impregnated towelettes of the present invention contains about 90 to about 97 weight percent water.

The wax-impregnated towelettes of the present invention are preferably impregnated with the aqueous silicone-based car wax emulsion in an amount in the range of about 30 grams (about 1 oz.) per square meter to about 170 grams (about 6 oz.) per square meter, more preferably about 30 to about 140 grams of emulsion per square meter of fabric.

Preferably, the moist wax-impregnated towelettes are packaged in containers or pouches that are substantially moisture-tight to prevent the wipes from drying out. Individual wax-impregnated towelettes may be packaged, in disposable, sealed, single-use pouches. Alternatively, a plurality of wipes may be packaged in a multi-use, moisture-tight, resealable, dispensing container. Typically, a moist wax-impregnated towelette has a size and shape that is

convenient for hand-polishing of a vehicle surface, for example a rectangular sheet of about 7 inches by 16 inches, or square or circular sheet of similar area.

Alternatively, the moist wax-impregnated towelettes may be packaged in a continuous roll form in a resealable, dispensing container having a cutting device or tearing aid affixed to the container, such that a consumer could choose the size of the wipe convenient for a given polishing job by tearing off a desired portion of the roll. The continuous roll of wipes may also be provided with perforations across the width of the roll at regular intervals along the length of the roll, such that one or more wipes may be torn from the roll without the need for a cutting aid.

The moist wax-impregnated towelettes may have a substantially flat, even surface or may have a dimpled, ridged, or otherwise textured surface. Preferred is a bonded or embossed melt blower polypropylene web.

The moist wax-impregnated towelettes of the present invention may be manufactured by combining a pre-cut, rolled length of the material with an aliquot of car wax emulsion, for example about 30 grams per square meter to about 170 grams per square meter. A roll coating technique, known in the art, can be utilized as well. The silicone polyether wetting agent in the aqueous silicone-based car wax emulsion facilitates penetration and even distribution of the emulsion into the fabric.

Example 1. Wax-impregnated Towelette Formulation A

Sheets of melt-blown polypropylene non-woven fabric (7 inches wide by about 16 inches long) having a weight of about 30 grams per square meter were substantially uniformly impregnated with about 140 grams of aqueous silicone-based car wax emulsion per square meter of fabric. The aqueous car wax emulsion contained about 95 weight percent water, about 3 weight percent isopropanol, about 0.8 weight percent silicone oil, about 0.13 weight percent amino-functional silicone, about 0.1 weight percent of cationic emulsifier, about 0.04 weight percent nonionic surfactant, about 0.28 weight percent silicone polyether wetting agent, about 0.06 weight percent antistatic agent, about 0.2 weight percent preservative, about 0.26 weight percent solvent, and about 0.003 weight percent wax.

The following components were utilized in Example 1 hereinabove:

5 The silicone oil was a 3:1:1 blend of silicone oils having viscosities of about 20, 350 and 1000 cSt respectively, which corresponds to an aggregate viscosity of about 80 cSt.

The amino-functional silicone was an aminoethylaminopropyl polydimethylsiloxane having a viscosity of about 10 to about 50 cSt and an amine content of about 0.48 milliequivalents of base per gram of polymer, available under the designation SF-1706 from GE Silicones of Waterford, New York.

10 The silicone polyether was a 1:10 by weight mixture of Silwet® L-7602 available from OSi Specialties, Inc. of Danbury, CT and SF1488 available from GE Silicones of Waterford, NY. According to the manufacturer's product bulletin and MSDS, SF1488 is an ethoxylated polydimethylsiloxane, wherein the ethoxylated portion of the polymer is terminated by 3-hydroxypropyl group, with  
15 a typical viscosity of 10 to 50 cSt at 25 °C, having CAS Registry No. 102783-01-7. Silwet® polymers are described by the manufacturer's product bulletin as block copolymers which are polyalkylene oxide-modified polydimethylsiloxanes.

20 The cationic emulsifier was a mixture of a quaternary amine a bis(2-hydroxyethyl) soyamine and a hydrogenated tallow amine acetate in a weight ratio of about 100:33:1 respectively.

25 The solvent was a 11:1 mixture by weight of mineral oil to butyl cellosolve; the wax was carnauba wax; the preservative was Busan® 77, available from Buckman Laboratories, Memphis, TN; and the antistatic agent was Larostat 264A, available from BASF Corp., Mount Olive, NJ.

30 The wax-impregnated towelette of Example 1 was utilized for polishing a dry, lightly soiled automobile exterior surface. An even, high-gloss finish was obtained without any visible scratching of the finish. Exterior surfaces that can be polished in this manner include painted surfaces, plastic surfaces, metal trim and similar non-porous automobile body parts.

Numerous variations and modifications of the embodiments described above may be effected without departing from the spirit and scope of

the novel features of the invention. It is to be understood that no limitations with respect to the specific embodiments illustrated herein are intended or should be inferred. It is, of course, intended to cover by the appended claims all such modifications as fall within the scope of the claims.

5

11  
 12  
 13  
 14  
 15  
 16  
 17  
 18  
 19  
 20  
 21  
 22  
 23  
 24  
 25  
 26  
 27  
 28  
 29  
 30  
 31  
 32  
 33  
 34  
 35  
 36  
 37  
 38  
 39  
 40  
 41  
 42  
 43  
 44  
 45  
 46  
 47  
 48  
 49  
 50  
 51  
 52  
 53  
 54  
 55  
 56  
 57  
 58  
 59  
 60  
 61  
 62  
 63  
 64  
 65  
 66  
 67  
 68  
 69  
 70  
 71  
 72  
 73  
 74  
 75  
 76  
 77  
 78  
 79  
 80  
 81  
 82  
 83  
 84  
 85  
 86  
 87  
 88  
 89  
 90  
 91  
 92  
 93  
 94  
 95  
 96  
 97  
 98  
 99  
 100  
 101  
 102  
 103  
 104  
 105  
 106  
 107  
 108  
 109  
 110  
 111  
 112  
 113  
 114  
 115  
 116  
 117  
 118  
 119  
 120  
 121  
 122  
 123  
 124  
 125  
 126  
 127  
 128  
 129  
 130  
 131  
 132  
 133  
 134  
 135  
 136  
 137  
 138  
 139  
 140  
 141  
 142  
 143  
 144  
 145  
 146  
 147  
 148  
 149  
 150  
 151  
 152  
 153  
 154  
 155  
 156  
 157  
 158  
 159  
 160  
 161  
 162  
 163  
 164  
 165  
 166  
 167  
 168  
 169  
 170  
 171  
 172  
 173  
 174  
 175  
 176  
 177  
 178  
 179  
 180  
 181  
 182  
 183  
 184  
 185  
 186  
 187  
 188  
 189  
 190  
 191  
 192  
 193  
 194  
 195  
 196  
 197  
 198  
 199  
 200  
 201  
 202  
 203  
 204  
 205  
 206  
 207  
 208  
 209  
 210  
 211  
 212  
 213  
 214  
 215  
 216  
 217  
 218  
 219  
 220  
 221  
 222  
 223  
 224  
 225  
 226  
 227  
 228  
 229  
 230  
 231  
 232  
 233  
 234  
 235  
 236  
 237  
 238  
 239  
 240  
 241  
 242  
 243  
 244  
 245  
 246  
 247  
 248  
 249  
 250  
 251  
 252  
 253  
 254  
 255  
 256  
 257  
 258  
 259  
 260  
 261  
 262  
 263  
 264  
 265  
 266  
 267  
 268  
 269  
 270  
 271  
 272  
 273  
 274  
 275  
 276  
 277  
 278  
 279  
 280  
 281  
 282  
 283  
 284  
 285  
 286  
 287  
 288  
 289  
 290  
 291  
 292  
 293  
 294  
 295  
 296  
 297  
 298  
 299  
 300  
 301  
 302  
 303  
 304  
 305  
 306  
 307  
 308  
 309  
 310  
 311  
 312  
 313  
 314  
 315  
 316  
 317  
 318  
 319  
 320  
 321  
 322  
 323  
 324  
 325  
 326  
 327  
 328  
 329  
 330  
 331  
 332  
 333  
 334  
 335  
 336  
 337  
 338  
 339  
 340  
 341  
 342  
 343  
 344  
 345  
 346  
 347  
 348  
 349  
 350  
 351  
 352  
 353  
 354  
 355  
 356  
 357  
 358  
 359  
 360  
 361  
 362  
 363  
 364  
 365  
 366  
 367  
 368  
 369  
 370  
 371  
 372  
 373  
 374  
 375  
 376  
 377  
 378  
 379  
 380  
 381  
 382  
 383  
 384  
 385  
 386  
 387  
 388  
 389  
 390  
 391  
 392  
 393  
 394  
 395  
 396  
 397  
 398  
 399  
 400  
 401  
 402  
 403  
 404  
 405  
 406  
 407  
 408  
 409  
 410  
 411  
 412  
 413  
 414  
 415  
 416  
 417  
 418  
 419  
 420  
 421  
 422  
 423  
 424  
 425  
 426  
 427  
 428  
 429  
 430  
 431  
 432  
 433  
 434  
 435  
 436  
 437  
 438  
 439  
 440  
 441  
 442  
 443  
 444  
 445  
 446  
 447  
 448  
 449  
 450  
 451  
 452  
 453  
 454  
 455  
 456  
 457  
 458  
 459  
 460  
 461  
 462  
 463  
 464  
 465  
 466  
 467  
 468  
 469  
 470  
 471  
 472  
 473  
 474  
 475  
 476  
 477  
 478  
 479  
 480  
 481  
 482  
 483  
 484  
 485  
 486  
 487  
 488  
 489  
 490  
 491  
 492  
 493  
 494  
 495  
 496  
 497  
 498  
 499  
 500  
 501  
 502  
 503  
 504  
 505  
 506  
 507  
 508  
 509  
 510  
 511  
 512  
 513  
 514  
 515  
 516  
 517  
 518  
 519  
 520  
 521  
 522  
 523  
 524  
 525  
 526  
 527  
 528  
 529  
 530  
 531  
 532  
 533